



DIFFERENTIAL CORRECTION RECEIVER WITH BLUETOOTH WIRELESS TECHNOLOGY

MobileMapper Beacon

MobileMapper™ Beacon complements the Thales Navigation mobile mapping family of products by improving real-time positioning accuracy with broadcast DGPS corrections. This differential receiver with Bluetooth® wireless technology provides access to standard RTCM SC-104 DGPS corrections broadcast by beacon networks around the world.

Advanced signal processing allows the MobileMapper Beacon to deliver reliable DGPS data from beacon broadcasts, even in noisy environments. Used together with MobileMapper CE, MobileMapper Beacon may be configured through a simple Windows® CE application, which enables automatic or manual tuning of the receiver and monitoring of operational and performance status.

Powered by four AA batteries, MobileMapper Beacon is compact and conveniently fits into a belt-mounted holster for easy, hands-free portability. MobileMapper Beacon employs an internal H-field antenna to provide superior signal reception in challenging environments, and integrated Bluetooth wireless technology to offer users cable-free connectivity to MobileMapper CE and other devices featuring Bluetooth wireless technology.

Compact, rugged and affordable, MobileMapper Beacon offers the most demanding GPS users cable-free convenience and reliability in the field.



MOBILEMAPPER BEACON

TECHNICAL SPECIFICATIONS

Receiver Characteristics

- Channels: 2 independent channels
- Frequency input: 283.5 to 325.0 kHz
- Channel spacing: 500 Hz
- Modulation: Minimum shift keying (MSK)
- MSK data rates: 100 and 200 bps
- Dynamic range: 100 dB
- Selectivity: > 60 dB at 400 Hz offset
- Operation modes: manual and automatic
- Internal antenna: H-field

Communication Characteristics

- Data output: RTCM SC-104
- Serial RS232 support
- Port settings: 4800 baud, 8 data bits, 1 stop bit, no parity
- Bluetooth wireless technology
 - Bluetooth specification: 1.1
 - Bluetooth power class: 1
 - Profile: Standard serial port

Physical Characteristics

- Size: 4.75" W x 4.95" L x 4.95" H
(12.07 cm W x 12.57 cm L x 12.57 cm H)
- Weight: 0.58 kg (1.27 lbs) including 4 AA alkaline batteries, no pouch

User Interface

- Power Button - On/Off push-button
- LED indication: Power - red, beacon lock - green, Bluetooth connection - Blue
- Advanced configuration setup and diagnostics via DGPS Configuration (MobileMapper CE software utility)

Power Characteristics

- Input Voltage: 4.0 to 6.0 VDC
- Batteries: 4 AA batteries, alkaline or NiMH
- Battery life: 8 hours continuous at 0° C
- Nominal current: 130 mA
- RF Connector: SMA socket
- Antenna Impedance: 50 ohms

Environmental Characteristics

- Environmental Protection: IEC-529 IPX5
- Operating Temperature: -30° C to +70° C operating, excluding battery effects
- Storage Temperature: -40° C to +80° C, excluding batteries
- Humidity: 100% condensing, ingress protection to IPX5

Standard Accessories

- 2 battery clips
- Pouch
- 4 AA batteries
- PC interface cable
- Printed manual

Optional Accessories

- External H-field loop DGPS beacon antenna 3.3 VDC
- External RF cable (SMA to TNC)



Thales Navigation, Inc.

Mobile Mapping Contact Information

North American Headquarters, San Dimas, CA, USA

+1 909 394 5000 • Fax +1 909 394 7050

Toll Free (Sales in USA/Canada) 1 800 922 2401

In South America +56 2 234 56 43 • Fax +56 2 234 56 47

Email mobilmapping@thalesnavigation.com

Asian Headquarters, Singapore

+65 6235 3678 • Fax +65 6235 4869

In China +86 10 6566 9866 • Fax +86 10 6566 0246

Email mobilmappingasia@thalesnavigation.com

Web site www.thalesnavigation.com

Thales Navigation follows a policy of continuous product improvement; specifications and descriptions are thus subject to change without notice. Please contact Thales Navigation for the latest product information.

©2004 Thales Navigation, Inc. All right reserved. MobileMapper is a trademark of Thales Navigation. All other product and brand names are trademarks or registered trademarks of their respective holders. Rev (7.26.04) P/N 830409A